



## NPN General Purpose Amplifier



**SOT-23**

### Features

- Moisture sensitivity level 1
- Halogen free and RoHS compliant
- Surface mount package ideally suited for automatic insertion

### Application

- Signal amplification
- Switching circuit

### Mechanical data

- **Package:** SOT-23
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102

### ■ Maximum Ratings ( $T_a=25^\circ\text{C}$ Unless otherwise specified)

Item	Symbol	Unit	Conditions	Value
Device marking code				1AM
Collector-base voltage	$V_{CB0}$	V	$I_C=10\mu\text{A}, I_E=0$	60
Collector-emitter voltage	$V_{CE0}$	V	$I_C=1\text{mA}, I_B=0$	40
Emitter-base voltage	$V_{EB0}$	V	$I_E=10\mu\text{A}, I_C=0$	6
Collector current	$I_C$	mA		200
Power dissipation	$P_D$	mW		350
Junction temperature	$T_J$	$^\circ\text{C}$		-55 to +150
Storage temperature	$T_{STG}$	$^\circ\text{C}$		-55 to +150



# MMBT3904

RoHS  
COMPLIANT

## ■ Electrical Characteristics (T<sub>a</sub>=25°C Unless otherwise specified)

Item	Symbol	Unit	Conditions	Min	Typ	Max
Collector-base breakdown voltage	V <sub>(BR)CBO</sub>	V	I <sub>C</sub> =10μA, I <sub>E</sub> =0	60		
Collector-emitter breakdown voltage	V <sub>(BR)CEO</sub>	V	I <sub>C</sub> =1mA, I <sub>B</sub> =0	40		
Emitter-base breakdown voltage	V <sub>(BR)EBO</sub>	V	I <sub>E</sub> =10μA, I <sub>C</sub> =0	6		
Collector-base cut-off current	I <sub>CBO</sub>	nA	V <sub>CB</sub> =60V			50
Collector-emitter cut-off current	I <sub>CEX</sub>	nA	V <sub>CE</sub> =30V, V <sub>EB</sub> =3V			50
DC current gain	h <sub>FE1</sub>		V <sub>CE</sub> =1V, I <sub>C</sub> =0.1mA	40		
	h <sub>FE2</sub>		V <sub>CE</sub> =1V, I <sub>C</sub> =1mA	70		
	h <sub>FE3</sub>		V <sub>CE</sub> =1V, I <sub>C</sub> =10mA	100		300
	h <sub>FE4</sub>		V <sub>CE</sub> =1V, I <sub>C</sub> =50mA	60		
	h <sub>FE5</sub>		V <sub>CE</sub> =1V, I <sub>C</sub> =100mA	30		
Collector-emitter saturation voltage	V <sub>CE(sat)1</sub>	V	I <sub>C</sub> =10mA, I <sub>B</sub> =1mA			0.2
	V <sub>CE(sat)2</sub>	V	I <sub>C</sub> =50mA, I <sub>B</sub> =5mA			0.3
Base-emitter saturation voltage	V <sub>BE(sat)1</sub>	V	I <sub>C</sub> =10mA, I <sub>B</sub> =1mA	0.65		0.85
	V <sub>BE(sat)2</sub>	V	I <sub>C</sub> =50mA, I <sub>B</sub> =5mA			0.95
Transition frequency	f <sub>T</sub>	MHz	V <sub>CE</sub> =20V, I <sub>C</sub> =10mA, f=100MHz	300		
Delay time	t <sub>d</sub>	ns	V <sub>CC</sub> =3V, I <sub>C</sub> =10mA, V <sub>BE</sub> =0.5V, I <sub>B1</sub> =1mA		35	
Rise time	t <sub>r</sub>	ns			35	
Storage time	t <sub>s</sub>	ns	V <sub>CC</sub> =3V, I <sub>C</sub> =10mA, I <sub>B1</sub> =-I <sub>B2</sub> =1mA		200	
Fall time	t <sub>f</sub>	ns			50	
Collector-base output capacitance	C <sub>ob</sub>	pF	V <sub>CB</sub> =5V, I <sub>E</sub> =0, f=1MHz			4
Emitter-base input capacitance	C <sub>ib</sub>	pF	V <sub>EB</sub> =0.5V, I <sub>C</sub> =0, f=1MHz			8

## ■ Thermal Characteristics

Parameter	Symbol	Unit	Value
Thermal resistance, junction-to-ambient	R <sub>θJ-A</sub> <sup>(1)</sup>	°C/W	357
Thermal resistance, junction-to-case	R <sub>θJ-C</sub> <sup>(1)</sup>	°C/W	286

### Note:

(1) Device mounted on PCB, single-sided copper, with standard footprint



■ Characteristics

Fig 1: Static Characteristics




Fig 2: DC Current Gain  $h_{FE}$




Fig 3: Collector-Emittor Saturation Voltage




Fig 4: Base-Emittor Saturation Voltage




Fig 5: Base-Emittor On Voltage





Fig 6:  $C_{ob}/C_{ib}-V_{CB}/V_{EB}$






# MMBT3904

RoHS  
COMPLIANT

Fig 7:  $P_D$ - $T_a$  Curve






# MMBT3904

RoHS  
COMPLIANT

## Ordering Information


Preferred P/N	Packing code	Unit weight(g)	Minimum package(pcs)	Inner box quantity(pcs)	Outer carton quantity(pcs)	Delivery mode
MMBT3904	F2	Approximate 0.008	3000	30000	120000	7" reel
MMBT3904	F4	Approximate 0.008	10000	/	210000	13" reel

## Outline Dimensions



SYMBOL	DIMENSIONS			
	INCHES		Millimeter	
	MIN.	MAX.	MIN.	MAX.
A	0.035	0.045	0.900	1.150
A1	0.000	0.004	0.000	0.100
A2	0.035	0.041	0.900	1.050
b	0.012	0.020	0.300	0.500
c	0.004	0.008	0.100	0.200
D	0.110	0.118	2.800	3.000
E	0.047	0.055	1.200	1.400
E1	0.089	0.100	2.250	2.550
e	0.037TYP		0.950TYP	
e1	0.071	0.079	1.800	2.000
L	0.022REF		0.550REF	
L1	0.012	0.020	0.300	0.500
θ	0°	8°	0°	8°

## Suggested Pad Layout





## Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function, or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.